





Tension fabric systems are the next generation in large format graphic displays. These light weight systems are highly portable and easy to set up, offering maximum impact with minimal fuss!

features & benefits

The HopUp Portable display system has a light weight, heavy duty frame that can suspend a fabric graphic mural. It sets up in seconds and can be packed away just as quickly! Available in many convenient sizes.

	 HopUP 2x1	 HopUP 2x2	 HopUP 3x2	 HopUP 1x3	 HopUP 2x3	 HopUP 3x3	 HopUP 4x3
Estimated Graphic Size W/Out Endcaps <small>See template for dimensions</small>	60.0625"w x 31"h (1526 x 787mm) + bleed	60.0625"w x 60.0625"h (1526 x 1526mm) + bleed	89.125"w x 60.0625"h (2264 x 1526mm) + bleed	31"w x 89.125"h (787 x 2264mm) + bleed	60.0625"w x 89.125"h (1526 x 2264mm) + bleed	89.125"w x 89.125"h (2264 x 2264mm) + bleed	118.1875"w x 89.125"h (3002 x 2264mm) + bleed
Recommended Substrate: Power Stretch - Dyesublimation Fabric							
Hardware							
width	60.0625"/1526mm	60.0625"/1526mm	89.125"/2264mm	30"/762mm	60.0625"/1526mm	89.125"/2264mm	120.125"
height	31"/787mm	60.0625"/1526mm	60.0625"/1526mm	89.125"/2264mm	89.125"/2264mm	89.125"/2264mm	89.125"/2264mm
footprint	60.0625"w/1526mm x 12"d/304.8mm	60.0625"w/1526mm x 12"d/304.8mm	89.125"w/2264mm x 12"d/304.8mm	31"w/787mm x 12"d/304.8mm	60.0625"w/1526mm x 12"d/304.8mm	89.125"w/2264mm x 12"d/304.8mm	118.1875"w x 12"d/304.8mm
Shipping dimensions	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)	35"w x 16"h x 16"d (889 x 406.4x 406.4mm)
weight	5.5lb / 2.5k	10.5lb / 4.8k	15lb / 6.8k	8lb / 3.6k	15lb / 6.8k	25lb / 11.3k	30lb / 13.6k

Hopup Assembly Instructions



1 Unpack contents of bag.



2 Frame, graphic and brace locks are attached.



3 Unfold frame till it is completely unretracted.



4 The graphic is fastened with velcro and unfolds as the frame opens.



5 Once frame is fully opened, snap together all brace locks to secure frame.



6 Graphic may be adjusted by using the Velcro fastening system.



7 The graphic presentation is ready.

To assemble unit with end caps



1 Once the Hopup is fully erected, end caps can be positioned.



2 Wrap the ends of the graphic around the end cap frame and fasten with Velcro system.

To disassemble unit with end caps



3 Repeat till all Velcro corners are attached to graphic.



4 Disconnect the end caps in order to collapse the unit to disassemble.



1 DISASSEMBLY: Open and remove all brace locks.



2 Remove velcro from endcaps. Collapse unit as in photo 2.